

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

STEP	FROM	TO	SOURCE IP	DESTINATION IP	SERVICE PORT
1	U1 (CLIENT)	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	S1 (SERVER)	U1	S1 (IF NAT IS REQUIRED); W1 (IF S1 SUPPORTS LOOPBACK OR ALIAS)	P1
3	S1	PACKETING ENGINE	S1 (IF NAT IS REQUIRED); W1 (IF S1 SUPPORTS LOOPBACK OR ALIAS)	U1	P1
4	PACKETING ENGINE	U1	W1	U1	P1


531

FIG. 5A

STEP	FROM	TO	SOURCE IP	DESTINATION IP	SERVICE PORT
1	U1	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	S1	U1	W1	P1
3	S1	PACKETING ENGINE	W1	U1	P1
4	PACKETING ENGINE	U1	W1	U1	P1

533

FIG. 5C



7/54

FIG. 5B

TABLE MAINTAINED BY PACKETING ENGINE									
RECEIVE PACKET INBOUND TO PACKETING ENGINE					SEND IT OUTBOUND FROM PACKETING ENGINE				
RECEIVED ON INTERFACE	SOURCE ADDRESS		DEST. IP ADDRESS	SERVICE PORT	SEND FROM INTERFACE	DEST. SYSTEM TYPE	SEND PACKET TO		
	MAC	IP					MAC	IP	
i ₀			W1	P1	i ₁	LOOPBACK	S1 _M	W1	
i ₁	S1 _M	W1		P1	i ₀	ROUTER			DEFAULT ROUTE

FIG. 5D

534




FIG. 5E

STEP	FROM	TO	SOURCE IP	DESTINATION IP	SERVICE PORT
1	U1	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	S1	U1	W1	P1
3	S1	PACKETING ENGINE	W1	U1	P1
4	PACKETING ENGINE	U1	W1	U1	P1

536

FIG. 5F

TABLE MAINTAINED BY PACKETING ENGINE						
RECEIVE PACKET INBOUND TO PACKETING ENGINE				SEND IT OUTBOUND FROM PACKETING ENGINE		
RCX ON INT.	SOURCE ADDRESS		DESTINATION IP ADDRESS	SERVICE PORT	SEND VIA INT.	DEST. SYSTEM TYPE
	MAC	IP				
I ₀			W1	P1	I ₁	ALIAS
I ₁	S1 _M	W1		P1	I ₀	ROUTER
						MAC
						S1 _M
						IP
						W1
						DEFAULT ROUTE

537

538

FIG. 5G

STEP	FROM	TO	SOURCE IP	DESTINATION IP	SERVICE PORT
1	U1	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	S1	U1	S1	P1
3	S1	PACKETING ENGINE	S1	U1	P1
4	PACKETING ENGINE	U1	W1	U1	P1

~539

FIG. 5I




FIG. 5H

TABLE MAINTAINED BY PACKETING ENGINE						
RECEIVE PACKET INBOUND TO PACKETING ENGINE			SEND IT OUTBOUND FROM PACKETING ENGINE			
RCX ON INT.	SOURCE IP ADDRESS	DESTINATION IP ADDRESS	SERVICE PORT	SEND VIA INT.	DEST. SYSTEM TYPE	SEND PACKET TO IP ADDRESS
I_0		$W1$	$P1$	I_1	NAT REQUIRED	$S1$
I_1	$S1$		$P1$	I_0 (AFTER REVERSE NAT SOURCE IP TO $W1$)	ROUTER	DEFAULT ROUTE

FIG. 5J

11/54




FIG. 6

STEP	FROM	TO	SOURCE IP	DESTINATION IP	PORT
PORT P1					
1	U1 (CLIENT)	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	S1 (SERVER)	U1	S1 (IF NAT IS REQUIRED); W1 (IF S1 SUPPORTS LOOPBACK OR ALIAS)	P1
3	S1	PACKETING ENGINE	S1 (IF NAT IS REQUIRED); W1 (IF S1 SUPPORTS LOOPBACK OR ALIAS)	U1	P1
4	PACKETING ENGINE	U1	W1	U1	P1
PORT P2					
1A	U1 (CLIENT)	PACKETING ENGINE	U1	W1	P2
2A	PACKETING ENGINE	S2 (SERVER)	U1	S2 (IF NAT IS REQUIRED); W1 (IF S2 SUPPORTS LOOPBACK OR ALIAS)	P2
3A	S1	PACKETING ENGINE	S2 (IF NAT IS REQUIRED); W1 (IF S1 SUPPORTS LOOPBACK OR ALIAS)	U1	P2
4A	PACKETING ENGINE	U1	W1	U1	P2

FIG. 6A

631

TABLE MAINTAINED BY PACKETING ENGINE									
RECEIVE PACKET INBOUND TO PACKETING ENGINE					SEND IT OUTBOUND FROM PACKETING ENGINE				
RCX ON INT.	SOURCE IP ADDRESS		DEST. IP ADDRESS	SERVICE PORT	SEND VIA INT.	DEST. SYSTEM TYPE	SEND PACKET TO		
	MAC	IP					MAC	IP	
I ₀			W1	P1	I ₁	LOOPBACK	S1 _M	W1	
						ALIAS	S1 _M	W1	
						NAT		S1	
I ₁	S1 _M	W1		P1	I ₀ (AFTER REVERSE NAT SOURCE IP TO W1)	ROUTER			DEFAULT ROUTE
	S1 _M	S1							
I ₀			W1	P2	I ₁	LOOPBACK	S2 _M	W1	
						ALIAS	S2 _M	W1	
						NAT		S2	
I ₁	S2 _M	W1		P2	I ₀ (AFTER REVERSE NAT SOURCE IP TO W1)	ROUTER			DEFAULT ROUTE
	S2 _M	S2							

FIG. 6B

632




FIG. 7

STEP	FROM	TO	SOURCE IP	DESTINATION IP	PORT
1	U1 (CLIENT)	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	FW (INTERFACE FW0)	U1	W1	P1
3	FW (INTERFACE FW1)	PACKETING ENGINE	U1	W1	P1
4	PACKETING ENGINE	VPN	U1	W1	P1
5	VPN	PACKETING ENGINE	U1	W1	P2
6A	PACKETING ENGINE	IDS	U1	W1	P2
6B	PACKETING ENGINE	APP1	U1	APP1 (IF NAT REQUIRED); W1 (IF LOOPBACK OR ALIAS SUPPORTED BY APP1)	P2
7	APP1	PACKETING ENGINE	APP1 (IF NAT REQUIRED); W1 (IF LOOPBACK OR ALIAS SUPPORTED BY APP1)	U1	P2
8A	PACKETING ENGINE	IDS	W1	U1	P2
8B	PACKETING ENGINE	VPN	W1	U1	P2
9	VPN	PACKETING ENGINE	W1	U1	P1
10	PACKETING ENGINE	FW (INTERFACE FW1)	W1	U1	P1
11	FW (INTERFACE FW0)	PACKETING ENGINE	W1	U1	P1
12	PACKETING ENGINE	U1	W1	U1	P1

FIG. 7A

TABLE MAINTAINED BY PACKETING ENGINE									
RECEIVE PACKET INBOUND TO PACKETING ENGINE					SEND IT OUTBOUND FROM PACKETING ENGINE				
RCX ON INT.	SOURCE ADDRESS		DEST. IP ADDRESS	SERVICE PORT	SEND VIA INT.	DEST. SYSTEM TYPE	SEND PACKET TO		
	MAC	IP					MAC		IP
I ₀			W1	P1	I ₁	TRANSPARENT	FW0 _M		W1
I ₂	FW1 _M		W1	P1	I ₂	TRANSPARENT	VPN _M		W1
I ₂	VPN _M		W1	P2	I ₁	TRANSPARENT	IDS _M		W1
					I ₃	LOOPBACK	APP1 _M		W1
						ALIAS	APP1 _M		W1
						NAT			APP1
I ₁	IDS _M			P2	I ₃	LOOPBACK	APP1 _M		W1
						ALIAS	APP1 _M		W1
						NAT			APP1
I ₃	APP1 _M	APP1 OR W1		P2	I ₁	TRANSPARENT	IDS _M		
					I ₂	TRANSPARENT	VPN _M		
I ₂	VPN _M	W1		P1	I ₂	TRANSPARENT	FW1 _M		
I ₁	FW0 _M	W1		P1	I ₀	ROUTER			DEFAULT ROUTE

FIG. 7B

732




FIG. 8

SERVICE PORT		APP1 PORT
P1		TP1

FIG. 8A

STEP	FROM	TO	SOURCE IP	DESTINATION IP	SERVICE PORT
1	U1 (CLIENT)	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	FW (INTERFACE FW0)	U1	W1	P1
3	FW (INTERFACE FW1)	PACKETING ENGINE	U1	W1	P1
4A	PACKETING ENGINE	IDS	U1	W1	P1
4B	PACKETING ENGINE	APP1	U1	APP1 (IF NAT REQUIRED); W1 (IF LOOPBACK OR ALIAS SUPPORTED BY APP1)	TP1
5	APP1	PACKETING ENGINE	APP1 (IF NAT REQUIRED); W1 (IF LOOPBACK OR ALIAS SUPPORTED BY APP1)	U1	TP1
6A	PACKETING ENGINE	IDS	W1	U1	P1
6B	PACKETING ENGINE	FW (INTERFACE FW1)	W1	U1	P1
7	FW (INTERFACE FW0)	PACKETING ENGINE	W1	U1	P1
8	PACKETING ENGINE	U1	W1	U1	P1

FIG. 8B

TABLE MAINTAINED BY PACKETING ENGINE									
RECEIVE PACKET INBOUND TO PACKETING ENGINE					SEND IT OUTBOUND FROM PACKETING ENGINE				
RCX ON INT.	SOURCE ADDRESS		DEST. IP ADDRESS	SERVICE PORT	SEND VIA INT.	DEST. SYSTEM TYPE	SEND PACKET TO		PORT
	MAC	IP					MAC	IP	
I ₀			W1	P1	I ₁	TRANSPARENT	FW0 _M	W1	P1
I ₂	FW _M		W1	P1	I ₁	TRANSPARENT	IDS _M	W1	P1
					I ₃	LOOPBACK	APP1 _M	W1	TP1
						ALIAS	APP1 _M	W1	TP1
						NAT		APP1	TP1
I ₁	IDS _M			P1	I ₃	LOOPBACK	APP1 _M	W1	TP1
						ALIAS	APP1 _M	W1	TP1
						NAT		APP1	TP1
I ₃	APP1 _M	APP1 OR W1		TP1	I ₁	TRANSPARENT	IDS _M		P1
					I ₂	TRANSPARENT	FW1 _M		P1
I ₁	FW _M	W1		P1	I ₀	ROUTER		DEFAULT ROUTE	P1

833

FIG. 8C




FIG. 9

STEP	FROM	TO	SOURCE IP	DESTINATION IP	PORT
1	U1 (CLIENT)	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	FIREWALL F1 (INT. FW0)	U1	W1	P1
3	FIREWALL F1 (INT. FW1)	PACKETING ENGINE	U1	W1	P1
4A	PACKETING ENGINE	IDS	U1	W1	P1
4B	PACKETING ENGINE	APP1	U1	APP1 (IF NAT); W1 (IF LOOPBACK OR ALIAS)	P1
5	APP1	PACKETING ENGINE	APP1 (IF NAT); W1 (IF LOOPBACK OR ALIAS)	U1	P1
6A	PACKETING ENGINE	IDS	W1	U1	P1
6B	PACKETING ENGINE	FIREWALL F1 (INT. FW1)	W1	U1	P1
7	FIREWALL F1 (INT. FW0)	PACKETING ENGINE	W1	U1	P1
8	PACKETING ENGINE	U1	W1	U1	P1
9	U1 (CLIENT)	PACKETING ENGINE	U1	W1	D1
10	PACKETING ENGINE	FIREWALL F1 (INT. FW0)	U1	W1	D1
11	FIREWALL F1 (INT. FW1)	PACKETING ENGINE	U1	W1	D1
12A	PACKETING ENGINE	IDS	U1	W1	D1
12B	PACKETING ENGINE	APP1	U1	APP1 (IF NAT); W1 (IF LOOPBACK OR ALIAS)	D1
13	APP1	PACKETING ENGINE	APP1 (IF NAT); W1 (IF LOOPBACK OR ALIAS)	U1	D1
14A	PACKETING ENGINE	IDS	W1	U1	D1
14B	PACKETING ENGINE	FIREWALL F1 (INT. FW1)	W1	U1	D1
15	FIREWALL F1 (INT. FW0)	PACKETING ENGINE	W1	U1	D1
16	PACKETING ENGINE	U1	W1	U1	D1

FIG. 9A

TABLES MAINTAINED BY PACKETING ENGINE									
RECEIVE PACKET INBOUND TO PACKETING ENGINE				SEND IT OUTBOUND FROM PACKETING ENGINE					
RCX ON INT.	SOURCE ADDRESS		DEST. IP ADDRESS	SERVICE PORT	SEND VIA INT.	DEST. SYSTEM TYPE	SEND PACKET TO		
	MAC	IP					MAC	IP	
I ₀			W1	P1 OR PORT IN RANGE OF 1025→1125	I ₁	TRANSPARENT	FW0 _M	W1	
I ₂	FW1 _M		W1	P1 OR PORT IN RANGE OF 1025→1125	I ₁	TRANSPARENT	IDS _M	W1	
					I ₃	LOOPBACK	APP1 _M	W1	
						ALIAS	APP1 _M	W1	
						NAT		APP1	
I ₁	IDS _M			P1 OR PORT IN RANGE OF 1025→1125	I ₃	LOOPBACK	APP1	W1	
						ALIAS	APP1 _M	W1	
						NAT		APP1	
I ₃	APP1 _M	APP1 OR W1		P1 OR PORT IN RANGE OF 1025→1125	I ₁	TRANSPARENT	IDS _M		
					I ₂	TRANSPARENT	FW1 _M		
I ₁	FW2 _M	W1		P1 OR PORT IN RANGE OF 1025→1125	I ₀	ROUTER			DEFAULT ROUTE

932

FIG. 9B




FIG. 9C

STEP	FROM	TO	SOURCE IP	DESTINATION IP	PORT
1	U1 (CLIENT)	PACKETING ENGINE	U1	W1	P1
2	PACKETING ENGINE	F1 (INT. FW0)	U1	W1	P1
3	F1 (INT. FW1)	PACKETING ENGINE	U1	W1	P1
4A	PACKETING ENGINE	IDS	U1	W1	P1
4B	PACKETING ENGINE	APP1	U1	APP1 (IF NAT REQUIRED); W1 (IF LOOPBACK OR ALIAS SUPPORTED BY APP1)	P1
5	APP1	PACKETING ENGINE	APP1 (IF NAT REQUIRED); W1 (IF LOOPBACK OR ALIAS SUPPORTED BY APP1)	U1	P1
6A	PACKETING ENGINE	IDS	W1	U1	P1
6B	PACKETING ENGINE	F1 (INT. FW1)	W1	U1	P1
7	F1 (INT. FW0)	PACKETING ENGINE	W1	U1	P1
8	PACKETING ENGINE	U1	W1	U1	P1
9	U1 (CLIENT)	PACKETING ENGINE	U1	APP1	D1
10	PACKETING ENGINE	F2 (INT. FW0)	U1	APP1	D1
11	F2 (INT. FW1)	PACKETING ENGINE	U1	APP1	D1
12A	PACKETING ENGINE	IDS	U1	APP1	D1
12B	PACKETING ENGINE	APP1	U1	APP1	D1
13	APP1	PACKETING ENGINE	APP1	U1	D1
14A	PACKETING ENGINE	IDS	APP1	U1	D1
14B	PACKETING ENGINE	F2 (INT. FW1)	APP1	U1	D1
15	F2 (INT. FW0)	PACKETING ENGINE	APP1	U1	D1
16	PACKETING ENGINE	U1	APP1	U1	D1

934

FIG. 9D

TABLES MAINTAINED BY PACKETING ENGINE									
RECEIVE PACKET INBOUND TO PACKETING ENGINE					SEND IT OUTBOUND FROM PACKETING ENGINE				
RCX ON INT.	SOURCE ADDRESS		DEST. IP ADDRESS	SERVICE PORT	SEND VIA INT.	DEST. SYSTEM TYPE	SEND PACKET TO		
	MAC	IP					MAC	IP	
I ₀			W1	P1	I ₁	TRANSPARENT	F1(FW0) _M	W1	
I ₂	F1(FW1) _M		W1	P1	I ₁	TRANSPARENT	IDS _M	W1	
					I ₃	LOOPBACK	APP1 _M	W1	
						ALIAS	APP1 _M	W1	
						NAT		APP1	
I ₁	IDS _M			P1	I ₃	LOOPBACK	APP1 _M	W1	
						ALIAS	APP1 _M	W1	
						NAT		APP1	
I ₃	APP1 _M	APP1 OR W1		P1	I ₁	TRANSPARENT	IDS _M		
					I ₂	TRANSPARENT	F1(FW1) _M		
I ₁	F1(FW0) _M	W1		P1	I ₀	ROUTER		DEFAULT ROUTE	
I ₀			APP1	PORT>1024	I ₁	TRANSPARENT	F2(FW0) _M	APP1	
I ₂	F2(FW1) _M		APP1	PORT>1024	I ₁	TRANSPARENT	IDS _M	APP1	
					I ₃	SERVER IP ADDRESS	APP1 _M	APP1	
I ₁	IDS _M			PORT>1024	I ₃	SERVER IP ADDRESS	APP1 _M	APP1	
I ₃	APP1 _M	APP1		PORT>1024	I ₁	TRANSPARENT	IDS _M		
					I ₂	TRANSPARENT	F2(FW1) _M		
I ₁	F2(FW0) _M	APP1		PORT>1024	I ₀	ROUTER		DEFAULT ROUTE	

FIG. 9E




FIG. 10





FIG. 11






FIG. 12




FIG. 13




FIG. 14

SERVICE IP ADDRESS W1

STEP W1-1	INTRUSION DETECTION	I1
STEP W1-2/3	FIREWALL	F5
STEP W1-4	APPLICATION SERVER	A4

1431

FIG. 14A

SERVICE IP ADDRESS W5

STEP W5-1/2	FIREWALL	F5
STEP W5-3	APPLICATION SERVER	A4

1432

FIG. 14B

SERVICE IP ADDRESS W1D

STEP W1D-1	DATABASE SERVER	D1
------------	--------------------	----

1433

FIG. 14C

SERVICE IP ADDRESS W5D

STEP W5D-1	DATABASE SERVER	D1
------------	--------------------	----

1434

FIG. 14D




FIG. 15




FIG. 15A




FIG. 15D




FIG. 16

38/54




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 17B




FIG. 17C




FIG. 17E

FIG. 17D




FIG. 17F




FIG. 17G

FIG. 17H




FIG. 171




FIG. 17J




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24